

Dimension Data - CTUA Range (All Models)

Model		22	30	35	40	50	60	75	90	100	115
'A' Width	[mm]	1075	1075	1075	1075	1075	1075	1327	1327	1327	1327
'B' Height	[mm]	610	610	610	610	895	895	1100	1100	1345	1345
'C' Support Spacing	[mm]	450	450	450	450	450	450	627	627	627	627
'D' Support Spacing	[mm]	312	312	312	312	312	312	312	312	312	312
'E' Support Spacing	[mm]	315	315	315	315	315	315	388	388	388	388
'F' Centre of Flue	[mm]	240	240	240	240	430	430	346	346	537	537
'G' Flue Center to Air Intake Center	[mm]	140	140	140	140	140	140	225	225	225	225
'H' Position of Flue	[mm]	218	218	218	218	211	211	260	260	260	260
'I' Gas Inlet Position	[mm]	150	150	150	150	150	150	220	220	220	220
Weight	[kg]	84	84	88	92	115	122	160	169	194	203
'Z' Length	[mm]	756	756	756	756	806	806	756	756	806	806
Mounting Height to Heater Base	[m]	Min. Recommended 2.5 Max. Recommended 3.5		Heaters may be mounted at a higher level if destratification fans and/or turn down nozzles are installed.							

Heater Clearances to Combustibles (mm)

Above Heater	Below Heater	To Side of Heater	To Rear of Heater	To Front of Heater	To Flue
150	300	500	600	3000	50

CTUB/C Specifications - (All Models)

All dimensions shown in mm.

